



SPECIFICATIONS

- Frequency Range : 1.0 - 3.0 GHz
- Coupling : 30 dB \pm 3 dB
- Coupling flatness \pm 2 dB
- Minimum Directivity : 20 dB
- Maximum Insertion Loss : 0.2 dB
- Maximum VSWR : 1.4 : 1
- Power Handling : 500 W CW (up to 1000 W CW at 25 °C)
10 kW peak
- Connectors : Main line input 7/16 Female
Main line output 7/16 Female
Coupling line SMA Female
- Operating Temperature : -40 to +85°C
- Storage Temperature : -55 to +125°C

		Matière : Aluminum		Titre : DUAL DIRECTIONAL COUPLER 1-3 GHz	
		Taitement : Black Painted		CD-2-1000-3000-30-30-716F-716F-SF	
		Classif. : 2		Document N° : CD-2-1000-3000-30-30-500-716F-716F-SF	
		Tolérance générale : \pm 0.5mm		Date : 06/03/2017 Dessiné par : smellaza	
		Echelle : 2 : 1		Feuille : 1 / 1	
Date	Indice	Nature de la modification		Niv. Sup.	



Ce document est la propriété de DETI S.A. Il ne peut être reproduit, ni communiqué à un tiers sans autorisation écrite de la dite société DETI S.A.