



### TECHNICAL SPECIFICATIONS

Frequency Range :	3300 - 18000 MHz
Insertion Loss :	1.0 dB max.
VSWR :	2.0:1 max.
3 dB cut off :	3 GHz
Shape factor (3dB-30dB) :	1.15
Max. input Power :	2 W CW
Operating Temperature :	-40°C to +70°C
Storage Temperature :	-55°C to +85°C
Input Connector :	SMA Female
Output Connector :	SMA Female

		Matière : Aluminum 5083	Titre :	
		Traitement : Silver plated	High Pass Filter 3.3 - 18 GHz	
		Classif. : 2	HPF-SS-3300-18000-1.15-SF-SF	
		Tolérance générale : ISO2768 - mK	Document N° : 800029 0A 1601A	
Date	Indice	Nature de la modification	Niv. Sup.	Echelle :
				3:1
				Feuille : 1 / 1
		Date : 26/09/2016		Dessiné par : smellaza
7, rue de Kérékou - 29200 BREST - TEL : 02.98.47.90.57 - FAX : 02.98.03.75.04 - E-mail : contact@deti-sa.com - Web : www.deti-sa.com				

Ce document est la propriété de DETI S.A. Il ne peut être reproduit, ni communiqué à un tiers sans autorisation écrite de la dite société DETI S.A.

