



SPECIFICATIONS

Frequency Range :	1200 - 1400 MHz
Insertion Loss Maximum :	0.6 dB
Insertion Loss Tracking :	± 0.25 dB
VSWR IN/OUT maximum :	1.4:1
Phase Balance :	± 5°
Isolation minimum :	18 dB
Output Power :	800 W average 8 kW peak power, 10% DC
Input connectors :	N Female
Output connector :	N Female
Operating temperature :	0 to 50°C
Storage temperature :	-40 to 125°C

		Matière : Aluminium	Titre : 8 way Power Combiner	
		Taitement : Black Painted	1200-1400MHz - 800 W CW	
		Classif. : 2	Document N° : CO-8-1200-1400-115-NF-NF	
		Tolérance générale : ± 0.1mm		Date : 15/04/2014
		Echelle : 1:3		Dessiné par : smellaza
Date	Indice	Nature de la modification	Niv. Sup.	Feuille : 1 / 1
7, rue de Kérélie - 29200 BREST - TEL : 02.98.47.90.57 - FAX : 02.98.03.75.04 - E-mail : contact@deti-sa.com - Web : www.deti-sa.com				



Ce document est la propriété de DETI S.A. Il ne peut être reproduit, ni communiqué à un tiers sans autorisation écrite de la dite société DETI S.A.